

AMENDMENTS TO THE CLAIMS:

This listing of claims will replace all prior versions, and listings, of claims in this application:

LISTING OF CLAIMS:

Claim 1. (Canceled).

2. (Currently Amended) The spare-wheel carrier according to claim [[1]] 12, further comprising a display unit configured to represent [[a]] the position of the spare-wheel carrier.

3. (Previously Presented) The spare-wheel carrier according to claim 2, wherein the display unit is arranged in an instrument cluster.

Claims 4 and 5. (Canceled).

6. (Currently Amended) The spare-wheel carrier according to claim [[5]] 12, further comprising an actuator assigned to the lock, the actuator operable in accordance with a grip switch.

Claim 7. (Canceled).

8. (Currently Amended) The spare-wheel carrier according to claim [[7]] 12, wherein the ball supports the striker.

9. (Currently Amended) The spare-wheel carrier according to claim [[7]] 12, wherein the complementary locking element includes a movable blocking part configured to block swivel of the ball sockets from a closed position into an open position and configured to release the locking element in accordance with at least one of displacement and tilt of the blocking part.

10. (Currently Amended) The spare-wheel carrier according to claim [[7]] 12, further comprising a catch hook configured to hold the ball sockets in a closed position in accordance with a weight of the catch hook.

11. (Currently Amended) The spare-wheel carrier according to claim [[7]] 12, wherein the locking element includes at least one lever arranged as a release mechanism.

12. (Previously Presented) A spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:

at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block functions of the motor vehicle in accordance with the position of the spare-wheel carrier,

wherein the sensor includes a lock having a touch-sensitive switch configured to detect the position of the spare wheel carrier, the lock configured to retain the position of the spare-wheel carrier;

wherein the lock includes at least one locking element, including a striker having a ball and a pin, and at least one complementary locking element, including at least two swivelable ball sockets, one of the at least one locking element and the at least one complementary locking element attached to the body of the motor vehicle, another one of the at least one locking element and the complementing locking element attached to the spare-wheel carrier; and

wherein the lock includes an emergency release device configured to manually release the spare-wheel carrier, the emergency release device including an emergency release lock including a striker having at least one rotatable actuator rotatable into at least one unlocked position and a locked position, in the unlocked position, at least one first lever arranged to release the spare-wheel carrier movable in accordance with displacement of the striker, in the locked position, the at least one first lever not movable in accordance with displacement of the striker.

13. (Original) The spare-wheel carrier according to claim 12, wherein the emergency release device includes at least one second lever positioned to operate the at least one first lever.

14. (Currently Amended) A ~~The spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:~~

~~at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block at least functions of the tailgate of the motor vehicle in accordance with the position of the spare-wheel carrier; according to claim 12, further comprising:~~

~~at least one bearing arranged on the body; and
an end switch assigned to the at least one bearing.~~

15. (Previously Presented) The spare-wheel carrier according to claim 14, further comprising a grip switch assigned to the tailgate, the tailgate operable as a function of the position of the spare-wheel carrier detected by the end switch.

16. (Currently Amended) A ~~The spare-wheel carrier for a motor vehicle, the spare-wheel carrier pivotable at a body of the motor vehicle and arranged in a region of a tailgate of the motor vehicle, comprising:~~

~~at least one sensor configured to detect at least one position of the spare-wheel carrier and to transmit the at least one position to a control unit, the control unit configured to enable and block at least functions of the tailgate of the motor vehicle in accordance with the position of the spare-wheel carrier; and according to claim 12, further comprising:~~

~~an arrangement configured to block operation of a rear window in accordance with [[a]] the lock of the spare-wheel carrier.~~

Claims 17 to 19. (Canceled).